

DHI-HY-SA21A-W2

Wireless Smoke Alarm



- Split-spectrum sensor technology
- Test and silence features in one single button
- Loud sound output over 85 dB(A) at 3 meters
- Low quiescent current consumption
- Surface-mount device (SMD) circuit board design
- Low battery warning signal

System Overview

Dahua Wireless Smoke Alarm provides battery-powered smoke detection and alarm functions within a single unit. Advanced electronics in conjunction with a photoelectric smoke sensing chamber provide early detection of smoke and high immunity against unwanted alarms. This kind of smoke alarm does not require a mains supply and is suitable for general residential applications. Timely notification of the smoke alarm can be displayed on DMSS App in real time.

Scene

Mainly applied for villas, shops, apartments, etc.

Technical Specification

Working Principle

| | |
|-----------------|---------------|
| Collection Type | Smoke |
| Sampling Period | 10 s |
| Sensor Type | Photoelectric |

Alarm

| | |
|--------------------------|---|
| Alarm Type | Smoke alarm, fault alarm, low battery warning |
| Alarm Volume | 85dB-90dB(A) at 3 m (9.84 ft) |
| Alarm Mode | Visual and audible alarm |
| Silence Function | Yes |
| Silence Duration | About 12 min |
| Alarm Response Threshold | 0.2 dB/m - 0.3 dB/m |

Technical Specification

Basic Parameters

| | |
|------------------|--|
| Indicator Light | Red and green LED indicator |
| Led Instructions | Standby: Green indicator flashes once per minute Alarm: Red indicator flashes once per second Fault: Red indicator flashes once per minute Low battery warning: Red indicator flashes once per minute |
| Coverage Area | When the height of the space is less than 8 m (3.28 ft), the protection area of a device is 20 m ² -40 m ² |

Power Supply

| | |
|-------------------|---|
| Battery Life | 3 year |
| Operating Voltage | 3V CR123A lithium battery (replaceable) |
| Operating Current | Monitoring current: ≤ 35uA Alarm current: ≤ 35mA |

Operating Ambient

| | |
|-----------------------|----------------------------------|
| Operating Environment | Indoor |
| Operating Temperature | -10°C to +55°C (+14°F to +131°F) |
| Operating Humidity | ≤ 95% RH (non condensing) |

Appearance

| | |
|--------------|-------------------------------------|
| Color | White |
| Casing | ABS |
| Dimensions | φ98 mm × H43.1 mm (φ3.85" × H1.70") |
| Weight | 140 g (0.30 lb) |
| Installation | Ceiling Mount |

Certifications

| | |
|---------------------|-----------------------|
| Certifications | TÜV and CE listed |
| Compliance Standard | EN 14604:2005+AC:2008 |


Wireless

| | |
|-------------------------|--|
| Carrier Frequency | 433.1 MHz–434.6 MHz |
| Communication Distance | Up to 1000 m (3280.84 ft) in an open space |
| Communication Mechanism | Two-way |
| Frequency Hopping | Yes |
| Encryption Mode | AES128 |


Ordering Information

| Type | Part Number | Description |
|-------------|-----------------|----------------------|
| Smoke Alarm | DHI-HY-SA21A-W2 | Wireless Smoke Alarm |

Installation



Dimensions (mm[inch])



Application

