

Cross-beam LED Digital Control Box











VOLUME ADJUSTABLE















- High sensitivity 33 zones (11vertical 3 lateral);
- Detect ferrous & non-ferrous metal objects;
- Pre-set 72 scene for easy operation;



Conform to Electricity EN60950 Safety Standard Conform to Radiation EN50081-1 Standard Conform to Anti-interference EN50082-1 Standard
















Product Specification

Overall Exterior Size	2165*828*349mm
Passageway Interior Size	2017*720*349mm
Operating Voltage	AC100V ~ 240V 50 / 60Hz
Power	12W
Operating Temperatures	-20°C ~ 65°C
Installation Environment	Width 100cm* Length 200cm (minimum range without metal)
Operating Frequency	1KHz to 15KHz
Max Output	72dBµA/m at 10m



Function Configuration


Detection Zones	11 Vertical Zones
Pass Count	0-9999
Alarm Count	0-9999
Metal Detection Accuracy Range	One-dollar coin
User Interface	Dual sets of bright red and green digital tube display +
	integrated four-button panel operation mode
Password Protection Function	5-digit password protection
Operating Frequency	0-99
Security Level	0-99
Sensitivity Level	0-400
Alarm Volume	0-99
Alarm Tone	1-99
Alarm Time	1-99
Scene Setting	72 preset scenes
Infrared Setting	0-Both groups OFF
	1-Front group ON
	2-Rear group ON
	3-Both groups ON
Left and right LED Bars	Interchangeable
LED Alarm Bars	Front 2 groups
Simultaneous detection and alarm in	2 Detection zones simultaneously alarm
multiple zones	



Optional Functions: The above zones can be equipped with the following functions

- □ Front and Rear Panel Alarm LED Lights
- □ Turnstile Connection

Interface Display



Anti-interference Reference Standard



Keep ≥80cm from the X-Ray machine


Keep ≥50cm between two units


Keep ≥10cm from the wall

Note: The above distances are for reference only, and the actual distances shall be subject to the performance accuracy of on-site debugging; the higher the sensitivity, the greater the distance interval, and the lower the sensitivity, the smaller the distance interval.




Test kits





Detection Zone



Package

Packaging:	Carton box
Package Size:	L2245xW635xH200mm
Volume:	0.29m³
Net weight:	24kg
Gross weight:	30kg

