



ZW-6Z

Side Panel Digital Control Box



ACCESS CONTROL
CONNECTING



LED LIGHT
INDICATOR



MODULAR
DESIGN



PASSWORD
PROTECTION



VOLUME
ADJUSTABLE



HIGH
PRECISION



LED
DISPLAY





SENSITIVITY
ADJUSTABLE

- 6 Zones for enhanced precision in threat detection;
- Perfect for space-constrained environments;
- Built to withstand daily use in high-traffic areas;
- User-friendly operation;
- 3 Years warranty;

Conform to Electricity EN60950 Safety Standard

Conform to Radiation EN50081-1 Standard


Conform to Anti-interference EN50082-1 Standard



ZW-6Z

Product Specification

| | |
|--------------------------|--|
| Overall Exterior Size | 2165*828*349mm |
| Passageway Interior Size | 2017*720*349mm |
| Operating Voltage | AC100V ~ 240V 50 / 60Hz |
| Power | 12W |
| Operating Temperatures | -20°C ~ 65°C |
| Installation Environment | Width 100cm* Length 200cm (minimum range without metal) |
| Operating Frequency | 1KHz to 15KHz |
| Max Output | 72dBμA/m at 10m |



Function Configuration


| Detection Zones | 6 Vertical Zones |
|--|--|
| Pass Count | 0-99999 |
| Alarm Count | 0-99999 |
| Metal Detection Accuracy Range | One-dollar coin |
| User Interface | Dual sets of bright red and green digital tube display + integrated four-button panel operation mode |
| Password Protection Function | 5-digit password protection |
| Operating Frequency | 0-99 |
| Security Level | 0-99 |
| Sensitivity Level | 0-400 |
| Alarm Volume | 0-99 |
| Alarm Tone | 1-99 |
| Alarm Time | 1-99 |
| Scene Setting | 72 preset scenes |
| Infrared Setting | 0-Both groups OFF 1-Front group ON 2-Rear group ON 3-Both groups ON |
| Left and right LED Bars | Interchangeable |
| LED Alarm Bars | Front 2 groups |
| Simultaneous detection and alarm in multiple zones | 2 Detection zones simultaneously alarm |

ZW-6Z


Optional Functions: The above zones can be equipped with the following functions

- ☐ Front and Rear Panel Alarm LED Lights
- ☐ Turnstile Connection


Interface Display




Anti-interference Reference Standard



Keep $\geq 80\text{cm}$ from the X-Ray machine



Keep $\geq 50\text{cm}$ between two units




Keep $\geq 10\text{cm}$ from the wall


Note: The above distances are for reference only, and the actual distances shall be subject to the performance accuracy of on-site debugging; the higher the sensitivity, the greater the distance interval, and the lower the sensitivity, the smaller the distance interval.

ZW-6Z

Test kits



Detection Zone



Package

| | |
|---------------|--------------------|
| Packaging: | Carton box |
| Package Size: | L2245xW635xH200mm |
| Volume: | 0.29m ³ |
| Net weight: | 24kg |
| Gross weight: | 30kg |

