

SF26P-LM




- 24*10/100Base-TX Ethernet Ports (PoE) + 2*Gigabit Uplink Ethernet Port.
- IEEE802.3af/at. Max PoE power of single port is 30W. Total PoE power budget is up to 225W.
- Support 3 working modes. (Default, VLAN, CCTV).
- Support 6KV surge immunity, 8KV ESD immunity and anti-interference function.




Introduction

The security exclusive 24 ports PoE Ethernet switch, providing 24*downlink PoE ports (IEEE802.3af/at) and 2*1000Mbps Uplink ports, fulfills the demand for HD IP surveillance. Equipped with the excellent performance of ESD, 6KV lightning protection and surge protection circuits, the PoE switch could operate stably in the harsh environment. With unique one-key smart function, users can enable the VLAN easily and keep the network storm, virus & cyber attack away from their system.


Application



Physical Features



Interface drawing



Specification

| Model | SF26P-LM |
|--------------------------|--|
| Downstream Ports | 24* 10/100Base-TX (PoE) |
| Uplink Ports | 2x 10/100/1000Base-T Ethernet Ports |
| Network Standard | IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3x |
| Switch Capacity | 8.8Gbps |
| Throughput | 6.4Mpps |
| Switch Processing Scheme | Store and Forward |
| Memory Buffer | 4M |
| MAC Table | 8K |
| PoE Standard | 802.3af/at(PSE) |
| PsE Type | End-span |
| Power Pin Assignment | 1/2(+), 3/6(-) |
| PoE Power Output | 54V DC, 30 watts max |
| PoE Budge | 225 watts max |
| One-key Smart | Default: Support Vlan passthrough, All port can be communicated freely. |
| | VLAN: Port 1-24 support PoE Watchdog, isolated respectively, but can communicate with Port G1-G2 |
| | CCTV: Port 1-24 support PoE Watchdog, 10M, with long transmission distance of 250 meters. |
| Lightning protection | 6KV Execute: IEC61000-4-5 |
| ESD | 6KV Contact discharge 8KV Air discharge Execute: IEC61000-4-2 |
| Power Supply | AC 100V~240V |
| Power Dissipation | < 250W (Include PoE) |
| Work temperature | -10°C~50°C |
| Storage temperature | -40°C~85°C |
| Humidity(Non-condensing) | 5%-95% |
| Dimension(L*W*H) | 440mm*180mm*44mm |
| Weight | 2.32Kg |
| Regulator | CE, FCC, ROHS |

Package List

| Designation | Quantity |
|----------------|----------|
| SF26P-LM | 1 |
| AC Power Cable | 1 |
| User Manual | 1 |

Related Products

| Designation | Model |
|--|----------|
| 8-Port 10/100Mbps+2 Gigabit uplink PoE Switch | SF10P-HM |
| 16-Port 10/100Mbps+2 Gigabit uplink PoE Switch | SF18P-LM |